definity™ COMPLETE

Technical Specification

CLICK® Scolmore GROUP

Product Code: SFBS722BK

Description: 20A Ingot Double Pole Plate Switch

Luckinslive 435275581





General Information

Dimensions (mm)	86 (W) x 86 (H) x 28 (D)
Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Screwless Complete
Finish	Brushed Stainless
Insert Colour	Black
Compatible Cover Plate	SCP422#
Materials	Cover Plate: Stainless Steel Insert: Polycarbonate Rear Housing: Urea Switch Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Anti Microbial Certified	No
Operating Voltage (AC)	250
Frequency (Hz)	50
Resistive Load Rating (A)	20
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Torque Value (Nm)	1.8
Terminal Capacity - Solid (mm^2)	3 x 2.5
Double Pole Switch	Yes
Twin Earth Terminals	Yes
Minimum Back Box Depth (mm)	35
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN