definity™ COMPLETE

Technical Specification

CLICK® Scolmore GROUP

Product Code: SFPW051PW

Luckinslive 435278708

Description: 13A Double Pole Switched Fused Connection Unit With Optional Flex Outlet





General Information

Dimensions (mm)	86 (W) x 86 (H) x 26 (D)		
Insert Dimensions (mm)	82.5 (W) x 82.5 (H) x 2.5 (D)		
Plate Dimensions (mm)	86 (W) x 86 (H) x 4 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Screwless Complete		
Colour	Polar White		
Insert Colour	Polar White		
Compatible Cover Plate	SCP151#		
Materials	Cover Plate: Polycarbonate	Insert: Polycarbonate	
	Rear Housing: Urea	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	35		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-4, BS 1362

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CE UKCA

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN