# Technical Specification

Product Code: VPAB423

Description: 10AX 3 Gang 2 Way Toggle Plate Switch

Luckinslive 389108843





## General Information

| | |
|---|---|
| Dimensions (mm) | 149 (W) x 91 (H) x 40 (D) |
| Plate Dimensions (mm) | 146 (W) x 88 (H) x 8 (D) |
| Dimensions With Gasket (mm) | 149 (W) x 91 (H) x 9 (D) |
| Plate Fixing Centres - Horizontal (mm) | 120.6 |
| Style | Victorian |
| Finish | Antique Brass |
| Gasket Colour | Black |
| Supplied Fixing Screw Finish | Polished Brass |
| Switch Finish | Antique Brass |
| Materials | Front Plate: Stainless Steel<br>Rear Housing: Nylon<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass<br>Gasket: Nylon<br>Switch Front & Nut: Cast Zinc<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>Earth Strap: Mild Steel |
| Anti Microbial Certified | No |
| Operating Voltage (AC) | 250 |
| Frequency (Hz) | 50 |
| Inductive Load Rating (AX) | 10 |
| Load Rating Comments | Suitable for Fluorescent or Inductive Loads |
| Termination Type | Screw |
| Terminal Size (mm) | 4.9 x 4.1 |
| Terminal Torque Value (Nm) | 1.2 |
| Terminal Capacity - Solid ($mm^2$) | 4 x 1.5 or 2 x 2.5 |
| Modular Rocker Switches | Yes |
| 2 Way Switch | Yes |
| Minimum Back Box Depth (mm) | 25 |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 20 |

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125AB for antique brass finish.

UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN