# Technical Specification

Product Code: VPBR1836BK  Luckinslive 407856129

Description: 13A Ingot 2 Gang Double Pole Switched Safety Shutter Socket Outlet With Outboard Rockers






## General Information

| | |
|---|---|
| Dimensions (mm) | 149 (W) x 91 (H) x 28 (D) |
| Plate Dimensions (mm) | 146 (W) x 88 (H) x 8 (D) |
| Dimensions With Gasket (mm) | 149 (W) x 91 (H) x 9 (D) |
| Plate Fixing Centres - Horizontal (mm) | 120.6 |
| Style | Victorian |
| Finish | Polished Brass |
| Insert Colour | Black |
| Gasket Colour | Black |
| Supplied Fixing Screw Finish | Polished Brass |
| Materials | Front Plate: Stainless Steel<br>Switch Cover: Stainless Steel<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass<br>Gasket: Nylon<br>Insert & Housing: Urea<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>Earth Strap: Mild Steel |
| Anti Microbial Certified | No |
| Operating Voltage (AC) | 250 |
| Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 |
| Termination Type | Screw |
| Terminal Size (mm) | Ø5 |
| Terminal Torque Value (Nm) | 2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 |
| Double Pole Switch | Yes |
| 3 Pin Safety Shuttered | Yes |
| Twin Earth Terminals | Yes |
| Minimum Back Box Depth (mm) | 25 |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 20 |

**Standards** BS 1363-2

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
The safety shutter will only fully open when all three BS 1363 plug-top pins engage correctly with the shutter. Inserting the earth pin alone will not open the live and neutral shutter like conventional socket shutters.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN