Technical Specification

Product Code: VPMB723BK

Luckinslive 435283227

Description: 20A Ingot Double Pole Plate Switch With Neon





General Information

Dimensions (mm)	91 (W) x 91 (H) x 28 (D)		
Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)		
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Victorian		
Finish	Matt Black		
Insert Colour	Black		
Gasket Colour	Black		
Supplied Fixing Screw Finish	Matt Black		
Materials	Front Plate: Stainless Steel	Insert & Housing: Urea	
	Switch Cover: Stainless Steel	Neon Lens: Polycarbonate	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass	
	Earth Strap: Mild Steel	Gasket: Nylon	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.8
Terminal Capacity - Solid (mm^2)	3 x 2.5		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Neon Indicator	Yes	Indicator Colour	Red
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN