
# Technical Specification

Product Code: VPPN520BK

Luckinslive 390051688

Description: 10A Ingot 3 Pole Fan Isolation Plate Switch



## General Information

| | |
|---|---|
| Dimensions (mm) | 91 (W) x 91 (H) x 23 (D) |
| Plate Dimensions (mm) | 88 (W) x 88 (H) x 8 (D) |
| Dimensions With Gasket (mm) | 91 (W) x 91 (H) x 9 (D) |
| Plate Fixing Centres - Horizontal (mm) | 60.3 |
| Style | Victorian |
| Finish | Pearl Nickel |
| Insert Colour | Black |
| Gasket Colour | Black |
| Supplied Fixing Screw Finish | Polished Chrome |
| Materials | Front Plate: Stainless Steel<br>Switch Cover: Stainless Steel<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Busbars: Formed Pressed Brass<br>Gasket: Nylon<br>Insert: Urea<br>Terminals: Brass<br>Contacts: Silver "on-lay" Copper / Brass<br>Earth Strap: Mild Steel |
| Anti Microbial Certified | No |
| Operating Voltage (AC) | 250 |
| Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 10 |
| Termination Type | Screw |
| Terminal Size (mm) | Ø3.5 |
| Terminal Torque Value (Nm) | 0.5 |
| Terminal Capacity - Solid ($mm^2$) | 4 x 1.5 or 2 x 2.5 |
| Modular Rocker Switches | No |
| Triple Pole Switch | Yes |
| Product Marking | Isolator, On, Off' |
| Minimum Back Box Depth (mm) | 16 |
| Ingress Protection | IP20 |
| Operational Temperature (°C) | -5 to +40 |
| Warranty (Years) | 20 |

**Standards** BS EN 60669-2-4, BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN