# Technical Specification

Product Code: VPSC050WH

Luckinslive 389115357

Description: 13A Fused Connection Unit With Optional Flex Outlet







## General Information

| | | | |
|---|---|---|---|
| Dimensions (mm) | 91 (W) x 91 (H) x 25 (D) | | |
| Plate Dimensions (mm) | 88 (W) x 88 (H) x 8 (D) | | |
| Dimensions With Gasket (mm) | 91 (W) x 91 (H) x 9 (D) | | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | | |
| Style | Victorian | | |
| Finish | Satin Chrome | | |
| Insert Colour | White | | |
| Gasket Colour | White | | |
| Supplied Fixing Screw Finish | Polished Chrome | | |
| Materials | Front Plate: Stainless Steel | Insert, Fuse Drawer & Housing: Urea | |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated | |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel | |
| | Gasket: Nylon | | |
| Anti Microbial Certified | No | | |
| Operating Voltage (AC) | 250 | Frequency (Hz) | 50 |
| Resistive Load Rating (A) | 13 | | |
| Fuse Fitted Type | Plug Top Cartridge Fuse | | |
| Termination Type | Screw | | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) | 2 |
| Terminal Capacity - Solid ($mm^2$) | 3 x 2.5 or 2 x 4 | | |
| Switched | No | | |
| Twin Earth Terminals | Yes | | |
| Product Marking | Fused | | |
| Flex Outlet Available | Yes | | |
| Flex Outlet Location | Front of Plate | Flex Outlet Dimension (mm) | Ø10 |
| Minimum Back Box Depth (mm) | 25 | | |
| Ingress Protection | IP20 | | |
| Operational Temperature (°C) | -5 to +40 | | |
| Warranty (Years) | 20 | | |

**Standards** BS 1363-4, BS 1362

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
**T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362
**E**: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN