Technical Specification

Product Code: VPSS512 Luckinslive 391865077

Description: 2 Tier MiniGrid® Unfurnished Plate - 12 Apertures



General Information

Plate Dimensions (mm)	146 (W) x 146 (H) x 8 (D)	
Dimensions With Gasket (mm)	149 (W) x 149 (H) x 9 (D)	
MiniGrid Plate (Gang)	12	
MiniGrid Single Width Module Quantity	12 (2 x 6)	
MiniGrid Double Width Module Quantity	6	
Style	Deco	
Finish	Stainless Steel	
Gasket Colour	Supplied With Both Black & White Gasket	
Supplied Fixing Screw Finish	Polished Chrome	
Materials	Front Plate: Stainless Steel	Gasket: Nylon
Anti Microbial Certified	No	
Termination Type	Screw	
Modular Rocker Switches	Yes	
Yoke Required	Yes (2 x GR100)	
Minimum Back Box Depth (mm)	47	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Interchangeable with modules in the MiniGrid Range.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN