essentials™

Technical Specification

Product Code: WA195WT

Luckinslive 437484163

Description: 1 Gang Illuminated Switch Locator Gasket



General Information

Dimensions (mm)	91.5 (W) x 91.5 (H) x 6.5 (D)		
Accessory Fixing Centres (mm)	60.3		
Gasket Colour	White		
Materials	Polycarbonate & PCBA		
Operating Voltage (AC)	200-240	Frequency (Hz)	
Load Rating (W)	0.6		
Flylead Cable Length (mm)	110		
Pre-wired Cable Specification	2 Core 22AWG (Both Red)		
LED Indicator	Yes	Indicator Colour	White
Cable Restraint Supplied	No		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	1		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
The gasket illuminates when the switch is in the Off position and turns Off when the switch is On.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Compatible with Mode, Part M, Deco+ & Curva Ranges.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN