essentials™

Technical Specification

Product Code: WA228

Description: 100A 2 Pole 5 x 35mm² Link Box

Luckinslive 389120520



General Information

Dimensions (mm)	115 (W) x 65 (D) x 55 (H)		
Colour	Black		
Materials	Body: Urea Terminal Screws: Steel and Yellow Passivated	Terminals: Brass	
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	100		
Number Of Terminals	5		
Termination Type	Screw		
Terminal Size (mm)	Ø8.7	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	1 x 35		
Cable Entry Dimensions (mm)	Ø9.7		
Ingress Protection	IP20		
Operational Temperature (°C)	-20 to +55		
Warranty (Years)	10		

Standards BS 5733

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Tamper Proof Sealable.
All moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC CLICK OR SCAN