essentials™


Technical Specification


Product Code: WA4147

Luckinslive 391253485

Description: 1 Gang 47mm Deep FlameGuard® Dry Lining Box







General Information

Dimensions (mm)	82 (W) x 82 (H) x 35 (D)		
Cutout Dimensions (mm)	73 (W) x 73 (H)		
Materials	Body: Galvanised Steel	Earth Terminal: Brass	
	Terminal Screw: Brass	Springs: Spring Steel	
	Pad Insert: Intumescent Composite		
Minimum Plasterboard Thickness (mm)	5		
Maximum Plasterboard Thickness (mm)	30		
Back Box Knockouts - Total (mm)	5 x Ø25		
Back Box Knockouts - Top (mm)	2 x Ø25	Back Box Knockouts - Bottom (mm)	2 x Ø25
Back Box Knockouts - Rear (mm)	1 x Ø25	Back Box Knockouts - Sides (mm)	None
Back Box Earth Terminal Supplied	Yes		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS 4662, BS EN 1364-1, BS EN ISO 10140-2

Regulations Part B (Fire)Up To 90 Minutes In Non-Loadbearing Studwall
Part E (Acoustic) & Complies with the requirements published in the Robust Details Part E Handbook

Scolmore House, Mariner, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7UL United Kingdom
T: +44 (0)1827 63454 | **F:** +44 (0)1827 63362
E: sales@scolmore.com | **W:** scolmore.com

CLICK OR SCAN Catalogue Range DoC Installation CLICK OR SCAN